



Quality is in our nature

PRODUCT INFORMATION

April 2015



EUROL BRAKEFLUID DOT 5 SILICONE

Silicone-based brake fluid for old-timers / go-karts / Harley Davidson

Eurol® Brake Fluid DOT 5 Silicone is a silicone-based brake fluid. The product has a broad temperature range (-40°C up to +260°C) and ensures optimum performance at low temperatures and a low toxicity.

Eurol® Brake Fluid DOT 5 Silicone helps to prevent corrosion and provides excellent lubrication to rubber seals and metals. It extends brake system life-cycle and will not affect paints.

Eurol® Brake Fluid DOT 5 Silicone can safely be used in hydraulic brake and clutch systems of cars, (racing) motorcycles, Harley Davidson bikes, go-karts, old-timers and in industrial applications.

NB: The old brake fluid has to be drained thoroughly from the system before re-fill.

Eurol® Brake Fluid DOT 5 Silicone should never be mixed with other brake fluids.

Eurol® Brake Fluid DOT 5 Silicone is not suitable for Citroën cars.

PERFORMANCE

Dep. of the Army
MIL-B-46176
FMVSS-116 DOT 5
Automotive All Weather
Attention:
Store in well closed packaging and avoid contamination with water and lubricants.

TYPICAL PROPERTIES

DOT 5		
Density 20C	Kg/L	0.95
Wet boiling point	C	>175
Dry boiling point	C	>255
Viscosity 100C	cSt	5.8
Viscosity -40C	cSt	103
Viscosity -60C	cSt	300
Vapour Lock	C	>260
Flash point	C	185

AVAILABLE VOLUMES

E801550 - 250ML, E801550 - 1L, E801550 - 60L, E801550 - 210L

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of Eurol products. The information in this document at any time and without notice be altered because of continuous product research and development. The analytical data are listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, the quality of the product does not affect. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product in consultation with the supplier.

