



Quality is in our nature

PRODUCT INFORMATION

April 2015



EUROL HD LUBE FOR PRIMARY CHAIN

Oil for Harley Davidson primary chaincase and diaphragm clutch

Eurol® HD Lube for Primary Chaincase has especially been formulated for the lubrication and protection of the primary chain case and the oil bath clutches. Even at extremely low temperatures, an optimal lubrication and a smooth cold start is guaranteed. Because of the special selected additives, rust, corrosion and deposits are reduced to a minimum and water will be repelled.

Eurol® HD Lube for Primary Chaincase maintains an extremely consistent lubricating film, even at high temperatures and high speeds. Therefore, offers an optimum protection.

Eurol® HD Lube for Primary Chaincase is very suitable for the lubrication of the Primary Chaincase of Harley Davidson models FL, FLT, FXR and FX with oil-bath clutch, from 1984.

It is also suitable for application in ATV's and Snowmobiles, for which such kind of oil is prescribed.

PERFORMANCE

TYPICAL PROPERTIES

Primary Chaincase		
Density 20C	Kg/L	0.870
Viscosity 100C	cSt	13.8
Viscosity 40C	cSt	96.4
Viscosity Index		145
Flash point COC	C	215
Pour point	C	-33

AVAILABLE VOLUMES

E110027 - 1L, E110027 - 4L, E110027 - 60L



The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of Eurol products. The information in this document at any time and without notice be altered because of continuous product research and development. The analytical data are listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, the quality of the product does not affect. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product in consultation with the supplier.