

A Division of Thiessen Products

INSTRUCTION SHEET FOR TOOL #2043



FORK NUT SOCKET

USE ON ALL WIDE GLIDE FORK TUBE PLUGS

- 1. Refer to Harley Davidson® Service Manual for specifications.
- 2. Remove top fork nut using JIMS® #2244.
- 3. Loosen bottom T-Stem pinch bolt, holding fork tube assembly.
- 4. Remove fork slider and tube assembly.
- 5. Carefully clamp tube assembly in vise, using soft jaws, so as not to damage fork tube.
- 6. WARNING: the fork tube plug is under pressure from fork spring. Be careful when removing plug to prevent bodily injury. Unscrew plug slowly, while applying downward pressure.

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS AND TOOL. SEE JIMS® CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS. THE LAST TOOLS YOU WILL EVER NEED TO BUY.

"From the Track... To the Street!"

555 DAWSON DRIVE, CAMARILLO, CA 93012 • PHONE 805-482-6913 • FAX 805-482-7422


No.2043-IS



Rev A 7 / 07

A Division of Thiessen Products

INSTRUCTION SHEET FOR TOOL #2043



FORK NUT SOCKET

USE ON ALL WIDE GLIDE FORK TUBE PLUGS

- 1. Refer to Harley Davidson® Service Manual for specifications.
- 2. Remove top fork nut using JIMS® #2244.
- 3. Loosen bottom T-Stem pinch bolt, holding fork tube assembly.
- 4. Remove fork slider and tube assembly.
- 5. Carefully clamp tube assembly in vise, using soft jaws, so as not to damage fork tube.
- 6. WARNING: the fork tube plug is under pressure from fork spring. Be careful when removing plug to prevent bodily injury. Unscrew plug slowly, while applying downward pressure.

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS AND TOOL. SEE JIMS® CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS. THE LAST TOOLS YOU WILL EVER NEED TO BUY.

"From the Track... To the Street!"

555 DAWSON DRIVE, CAMARILLO, CA 93012 • PHONE 805-482-6913 • FAX 805-482-7422