

INSTRUCTION SHEET FOR TOOL #2262

SPORTSTER & BUELL SPROCKET LOCKER TOOL

For use on all Sportsters 1991-2003

For use on all Buell Twins 1994-2002 **NOTE: NOT FOR USE ON XB MODELS** Use to remove the final drive belt sprockets on Sportsters & Buell's

CAUTION: NUT IS A LEFT HAND THREAD

- 1. Refer to H.D.® Service Manual for specifications.
- 2. To remove nut, insert handle of tool on top of the pivot shaft, inboard of the bottom frame tube and attach to sprocket.
- 3. Snugly tighten the thumb screw to hold tools position on the sprocket. CAUTION: DO NOT ALLOW SCREW TO MAR SPROCKET TEETH.
- 4. When tightening nut, the handle of the tool will contact the bottom of the pivot shaft. Tighten to H.D.® specifications using JIMS® Nut Sockets Tool (No. 94660-37A).

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS! SEE JIMS CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS. THE LAST TOOL YOU WILL EVER NEED TO BUY!

555 DAWSON DRIVE, CAMARILLO, CA 93012 PHONE 805-482-6913 • FAX 805-482-7422

No.2262-IS



REV N/C 3/05

INSTRUCTION SHEET FOR TOOL #2262



SPORTSTER & BUELL SPROCKET LOCKER TOOL

For use on all Sportsters 1991-2003

For use on all Buell Twins 1994-2002 **NOTE: NOT FOR USE ON XB MODELS** Use to remove the final drive belt sprockets on Sportsters & Buell's

CAUTION: NUT IS A LEFT HAND THREAD

- 1. Refer to H.D.® Service Manual for specifications.
- 2. To remove nut, insert handle of tool on top of the pivot shaft, inboard of the bottom frame tube and attach to sprocket.
- 3. Snugly tighten the thumb screw to hold tools position on the sprocket. CAUTION: DO NOT ALLOW SCREW TO MAR SPROCKET TEETH.
- 4. When tightening nut, the handle of the tool will contact the bottom of the pivot shaft. Tighten to H.D.® specifications using JIMS® Nut Sockets Tool (No. 94660-37A).

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS! SEE JIMS CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS. THE LAST TOOL YOU WILL EVER NEED TO BUY!